

associated with gravity anomalies, it makes sense to be sure there is a gravity anomaly to confirm the existence of a seismic structure.

There are still many structures, or prospects, to be leased and drilled offshore. The proper use of gravity data will greatly increase the ratio of successes to failures.

SEARLS, DAVID T., Vinson, Elkins, Weems & Searls, attorneys, Houston, Texas

#### NATURAL GAS REGULATION IN THE FUTURE

The pipeline transmission companies and producers may expect more liberal treatment in the future from the courts and the Federal Power Commission because this will be essential in the public interest. The Supreme Court, in the now famous CATCO case, directed the Commission to their responsibility under the Natural Gas Act to fix rates consistent with maintaining a supply of natural gas to the consumers.

We must assume that the courts and the Commission will not lose sight of this responsibility, but recent decisions disclose that this regulatory agency is not aware of the fact that they are faced at this time with maintaining a supply of natural gas to consumers.

The transmission companies must build and finance additional pipelines to meet increasing demands of consumers, but they have the problem today of obtaining the necessary funds at reasonable costs with the bloom being off pipeline investments. Consideration must be given to the depreciating rate base, rate of return, and other factors which determine the attractiveness of pipeline investments.

The Commission has recently followed the practice of not only using area pricing for the purpose of placing a lid on producers' prices, but also for rolling back existing area prices. The failure of many companies to bid on offshore acreage offered recently by the Federal Government and the State of Louisiana in areas known to contain proven or potential natural gas-producing acreage should be a warning that producers are losing their incentive to take the costly capital risks to drill for natural gas. This will have its effect on the supply of gas in 5 or 10 years. However, it is not believed that producers can hope for more liberal treatment until the Commission is convinced that there will be a shortage of natural gas in the near future.

SHOEMAKER, EUGENE M., U. S. Department of Interior, Branch of Astrogeology, Menlo Park, California

#### MANNED SPACEFLIGHT—A CHALLENGE TO GEOLOGISTS AND GEOPHYSICISTS

The advent of man in space opens new opportunities in the disciplines traditionally concerned with the surface and interior of the Earth. The synoptic view of the Earth's surface from an orbiting manned spacecraft affords a new avenue for investigation of regional geology. Considerable research and imagination are required to exploit it. The techniques developed may be expected to have important applications later in the exploration of Mars.

Men landing on the Moon will be able to apply the methods and instruments of geophysics and classical geology that are already well developed in the study of the Earth. Constraints of weight and time in spaceflight operations, however, require that considerable effort be spent in adapting these methods and instruments for optimum use in manned lunar missions. The ultimate results of this effort will include not only new knowledge about the Moon, but also new ideas, new techniques,

and light-weight sophisticated instruments that can be applied in the study of the Earth.

SHOCK, LORENZ I., Empire Geophysical, Inc., Midland, Texas

#### IMPACT SEISMIC TECHNIQUES

During the past few years there has been a general increase in the use of Impact Seismic Techniques to obtain geophysical data. In the extension and development of these techniques there has been some divergence from the original classic McCollum 2-patch technique. One such development has been the use of a large pattern of drops at a single drop area recorded by a standard multi-trace seismic unit. This is sometimes referred to as the "Mobil" technique. Another system in which a series of drop patterns are recorded along a standard seismic spread so as to provide for horizontal data stacking is designated the "Drop-Along" technique.

The relative merits of each of these techniques are discussed and their general areas of application outlined. Examples are presented showing results obtained by their use, as well as comparisons with each other and with standard shooting methods.

SHOR, GEORGE G., JR., Scripps Institution of Oceanography, La Jolla, California

#### CRUSTAL STRUCTURE UNDER THE CONTINENTAL TERRACE OF WESTERN NORTH AMERICA

Long reversed refraction profiles along the outer edge of the continental terrace have been made in numerous locations from Guatemala to the Bering Sea to determine the nature of the crustal section beneath the sediments. Off Guatemala, the structure is consistent with the theory that volcanic rocks and sediments have been laid down over a typical oceanic section, depressing the Moho as the upper surface built up to Pleistocene sea-level. Off western Alaska a thick section of material with granitic velocity is overlain by thick sediments; the Moho is down almost to continental depth, and the section appears to be similar to the adjacent continent.

Off the coasts of Canada, California, and Mexico, a more confusing structure is found. Depth to the Moho is between the Alaskan and Guatemalan values but does not show a progressive change. At some stations, the crustal velocities are similar to the continent; at other stations, crustal velocities are oceanic. In some places, the mantle velocity is abnormally low.

The depth to the Moho at all stations from Alaska to Guatemala is intermediate between continental and oceanic values. The mean depth is 21 km. From the data now on hand, one can only conclude that the crustal structure beneath the shelf is not uniform and cannot be reconciled with any simple hypothesis of either stability or growth of the continental mass.

SHORT, NICHOLAS M., Lawrence Radiation Laboratory, University of California, Livermore, California

#### TV BOREHOLE CAMERA—A VISUAL APPROACH TO GEOPHYSICAL LOGGING

In recent years, miniaturization of electronic components has led to development of "seeing-eye" TV cameras capable of entering small-diameter boreholes. Commercially available cameras now can operate in 3-inch holes to depths exceeding 5,000 feet. Some cameras look downhole; others view sideward by means of rotating mirrors. Built-in compass systems permit accurate surveys of hole orientation and attitudes of planar elements intersecting the borehole.

TV borehole cameras have many geological and engineering applications. In dry uncased holes, uses include determination of lithologic character and stratigraphic contacts, measurement of bedding and fracture orientation, identification of textural features (porosities), and establishment of causes of drilling problems including recognition of caved zones and intervals of circulation loss. A TV camera survey supplements or replaces coring. If hole walls are clean, inspection of the entire interval provides direct information normally lost where core recovery is poor. In holes containing buckled or perforated casing, lost tools or unknown obstructions, a TV traverse may guide the driller to an effective, time- and cost-saving remedy.

The Lawrence Radiation Laboratory has built two cameras for use in pre- and post-shot studies associated with underground nuclear explosions. These 2½-inch-diameter cameras can reach 3,000-foot depths and will operate in vertical or inclined holes up to diameters limited only by illumination capability. Both cameras have remote-control focussing. One camera, having a fixed side-viewing mirror, is equipped with a specially designed compass. The other camera looks down the axis of the hole. Field experience with these cameras is described and photos of the monitor image illustrate the results obtainable during in-hole operation. TV pictures showing the Gnome explosion cavity are compared with actual photographs taken inside this void.

The current status of TV borehole camera technology and possible future developments in both instrumentation and applications are reviewed.

SLACK, H. A., BRUNTON, G. D., LEE, H. C., ROSENFELD, M. A., AND CRAM, I. H., JR., Pure Oil Company, Research Center, Crystal Lake, Illinois

#### DEVELOPMENT OF THE COMMAP SYSTEM

COMMAP is an automatic mapping system. It uses an automatic map reader for digitizing the input data, an IBM 704 computer for processing the data and a Benson Lehner ElectropLOTter for plotting and contouring the output. This system processes, plots, and contours all mappable data. Computations which can be preformed by the system include the following: (1) determination of regionals and residuals by polynomial surface-fitting techniques, (2) determination of regionals and residuals by various ring-average methods, (3) upward and downward continuation of potential field data, (4) first and second vertical derivatives by several methods.

This paper covers the system in general and gives examples of tabulated, plotted and contoured output of the results for a number of specific field problems.

STANLEY, DANIEL G., Geology Branch, Soils Division, U. S. Army Engineer Waterways Experiment Station, Vicksburg, Mississippi

#### VERTICAL PETROGRAPHIC VARIABILITY IN ANNOT SANDSTONE TURBIDITES

A wide range of mineralogical and textural variations was observed between the base and the top of marine Tertiary Annot Sandstone turbidites in the Lac d'Allos region of the French Maritime Alps. This variability may be related to the characteristic vertical distribution of grain sizes and shapes within such graded deposits. Relative percentages of most light and heavy minerals and of the primary matrix, as well as factors of sphericity and roundness, are directly related to grain size. Thus the upward decrease in grain size and increase in grain sorting is reflected in a progressive change in rock composition. Samples (43) were collected at 4-cm

intervals between the base and top of four well graded turbidites, each less than one meter thick, and these were compared with spot samples (125) collected from a 250-m flysch section. The range of petrographic variability within a single turbidite is as great as the range of mineralogical and textural variations between the base and the top of the formation. The same minerals are found in each turbidite, indicating that source areas and eroded parent rock materials accumulated nearshore remained the same during the period of this formation's history. However, notable variations between succeeding turbidites were noted. This may be explained by the fact that each turbidity current is characterized by its own specific density and velocity gradient. As a result, differing proportions of particle sizes settled out of each suspension flow over the same spot on the ocean floor. Even though gravity currents are able to transport identical sedimentary materials from nearshore environments into the deeper basin, such quantitative variations should be expected in any formation composed of turbidites.

STUDER, H. P., Shell Development Company, Houston, Texas

#### ELECTRON MICROSCOPE STUDY OF ARAGONITE CRYSTALS IN MARINE SEDIMENTS

The occurrence of aragonite needles in the carbonate mud of the surface sediments of Florida Bay, the Florida Keys, and the Great Bahama Bank is of interest to problems of carbonate deposition. Older views regarding the origin of the aragonite needles support inorganic precipitation. More recent theories favor a biogenic formation and link the mud particles to the aragonite sheath of algae, mainly *Penicillus*, *Rhipocephalus*, and *Halimeda*. Electron microscope studies of mud suspensions and of aragonite crystals from *Penicillus* reveal a remarkable similarity between the aragonite formed on the algal surface, and the aragonite in the carbonate mud. Surface replicas of aragonite sheath peeled from *Penicillus* show needle-like crystals scattered between a network of fiber- or film-like algal material. The closely interwoven system of plant material and aragonite needles supports the suggestion of the algal substrate acting as a matrix for the aragonite formation.

SWANN, DAVID H., Illinois State Geological Survey, Urbana, Illinois

#### LATE MISSISSIPPIAN RHYTHMIC SEDIMENTS OF THE MISSISSIPPI VALLEY\*

Late Valmeyeran and Chesterian sediments that repeatedly filled the subsiding Illinois basin are a quarter autochthonous carbonate, a quarter sand, and half mud brought from remote northeastern sources by a major river system, the Michigan River. These are arranged in cycles implying shoreline fluctuation landward (north-eastward) and seaward through a range of a few hundred miles. About 70 minor reversals in shoreline movement are superimposed on about 15 major cycles. Increases in competence, perhaps in phase with modest lowering of sea-level, repeatedly changed the Michigan River into a prograding stream, pushing its delta scores of miles across a marine basin only a few tens of feet deep. Advancing distributaries carved grooves well below sea-level through frontal and lateral mud banks—grooves later filled by elongate sand bodies analogous with modern barfingers and pass fillings. In late stages the delta supported land vegetation. The carbonate phase

\* Published by permission of the chief of the Illinois State Geological Survey.