

Characterizing earthquake source physics with source scanning algorithms

FRÉDÉRIK MASSIN AND ALISON MALCOLM

Department of Earth Sciences, Memorial University of Newfoundland, 300 Prince Philip Drive, St. John's, Newfoundland and Labrador, A1B 3X5, Canada

Earthquake swarms that lack a clear main-shock are particularly difficult to explain and characterize for hazard assessment. These events could be triggered in the vicinity of a local perturbation from many sources, natural or not, with implications for our understanding of the rupture characteristics of earthquakes. We tackle the problem of understanding perturbing mechanisms, by investigating the location, mechanism and extent of earthquake ruptures. Shift and stack methodologies (or source scanning algorithm, SSA) are innovative methods for probabilistic analysis of earthquake sources using continuous seismic records. We investigate the potential of SSA for the probabilistic analysis of focal mechanisms.

SSA for earthquake location is based on three steps: (1) pre-calculation of travel time grids (also defining the hypocenter solution space), (2) calculating a characteristic function of the body-wave arrivals from continuous data, with signal processing methods, and (3) the shifting and summation of the characteristic functions in each grid cell, with shifts defined by the pre-calculated travel times. Ideally, the power recovered by the entire network as a function of time can be used for simultaneous event detection and location. Although the SSA method shows promise for automatic detection and location of events, it is limited by the precision of the pre-defined grid.

We extend this approach to focal mechanism determination with slight modifications. We first precalculate the polarity distribution for all double couple orientations. Then polarity corrections are applied to the first motion wavelets (as extracted with SSA) from all possible mechanisms. For the optimal orientation, the wavelets with downward first motions are multiplied by negative polarities and thus all wavelets stack constructively. Finally, the probability of each double couple orientation is estimated by stacking the modified wavelets.