

and remain within the drinking standards of the U.S. Public Health Service.

BROWN, R. F., and D. C. SIGNOR, U.S. Geol. Survey, Lubbock, Tex.

ARTIFICIAL RECHARGE—STATE OF THE ART

The largest potential reservoir for the storage of potable water is that which exists in the unsaturated zone. Utilization of this space for the storage and retrieval of potable water is a multifaceted problem which requires application of the best talent from the scientific community. Considerable research has taken place in artificial recharge since the last international symposium on the subject at Reading University, England, in 1970. An increasing demand for economic water supplies created by larger populations indicates a need for much greater research efforts in the near future.

Artificial recharge has many similarities to liquid-waste disposal through deep wells. In both, the problem is to place liquid into a permeable lithologic unit at an economic rate, to predict movement, and the chemical reactions and physical changes that take place while the liquid is in the reservoir. Differences between the two operations are principally in the type of fluid injected and the ultimate objective. In artificial recharge the objective is to store and retrieve water of good quality; in waste disposal the objective is to store permanently water of objectionable quality. In both artificial recharge and liquid-waste storage, the nature of the storage must be known, particularly that of the unsaturated zone. The techniques of investigation for recharge and waste disposal are generally the same.

Water commonly is recharged by surface spreading through basins, induced recharge from adjacent streams and lakes, or through injection wells. Research in recharge through basins has been dominated by mathematical models based on idealized conditions and empirical relations, derived by experimental sequencing of recharge operations, and operational controls in the pretreatment of recharge water. Recharge by injection wells has been undertaken in a variety of hydrologic environments, for example in Israel where efforts have been directed toward the analyses of diffusion and dispersion of the injected water. Much research in the United States has been directed toward the movement of bacteria and organic matter through an aquifer and in the chemical modeling of changes in recharged water as it moves.

Much more research is needed on the basic properties of aquifers, particularly in the unsaturated zone, and on all aspects of recharge water quality. Research and the utilization of data produced are increasingly the responsibility of interdisciplinary teams which consider the geologic, hydraulic, geochemical, bacteriologic, engineering, geophysical, and economic aspects of the system.

CHERRY, J. A., G. E. GRISAK, and R. E. JACKSON, Dept. of Earth Sci., Univ. Waterloo, Waterloo, Ont.

HYDROGEOLOGIC STUDIES AT A SUBSURFACE RADIOACTIVE-WASTE MANAGEMENT SITE IN WEST-CENTRAL CANADA

Nearly all radioactive wastes produced in Canada are stored or disposed of at 2 waste-management sites in shallow Quaternary deposits in south-central Canada. The oldest site and the one which has received most of Canada's radioactive waste is at the Chalk River Nuclear Laboratories (CRNL) in east-central Ontario. The newest site is at the Whiteshell Nuclear Research Establishment (WNRE) in southeastern

Manitoba. Both waste-management sites are operated by Atomic Energy of Canada Limited.

Hydrogeologic studies were conducted at WNRE to predict the subsurface behavior of radioactive contaminants, which at some future time possibly could enter the groundwater zone. The site is composed of Quaternary deposits of clayey till above a sandy artesian aquifer which overlies the Precambrian bedrock. The bedrock is 50 ft below ground surface. At present there is no significant contamination of the subsurface hydrogeologic environment. Hydrogeologic information is being used to facilitate the design and operation of the waste-management facilities and to assess long-term storage and disposal capabilities of the area.

The hydrogeologic investigations involved 3 main parameters. These are (1) expected residence times of radionuclides which may enter the groundwater flow system, (2) anticipated travel paths and discharge processes, and (3) suitability of the hydrogeologic environment for physical manipulation to achieve greater containment capabilities.

Hydrogeologic studies conducted during the past 5 years have involved field and laboratory techniques such as geologic test drilling, mapping of hydraulic head distributions using wells and piezometers, field permeability tests using single well response tests and long- and short-term pumping tests, mapping of natural hydrochemical patterns in the groundwater zone, tritium tracer experiments, groundwater age dating using C^{14} , and mathematical modeling using digital-simulation programs. Comparisons of the results from the studies indicate that we have attained a reasonable level of predictability in our understanding of the hydrogeologic environment in the area.

CLIFFORD, MICHAEL J., Ohio Geol. Survey, Columbus, Ohio

HYDRODYNAMICS OF MOUNT SIMON SANDSTONE, OHIO AND ADJOINING AREAS

The Mount Simon Sandstone (Cambrian), the most favorable stratum for waste injection in Ohio, presently accepts about 250×10^6 gal of industrial waste per year. Concern has been expressed about the transport of these fluids by natural hydrodynamic flow.

The potentiometric surface map of the Mount Simon reservoir of Ohio has a form which mirrors the structural configuration—highest values are in the deeper part of the Appalachian basin and lowest on the Indiana-Ohio platform. Flow direction in central Ohio is indicated to be west or northwest. Head difference is 2–7 ft. Porosity and permeability data combined with this information (Darcy's law) yield velocities of less than 6 in./year.

Because the assumptions involved in determining velocity in this manner are questionable, the resulting values should be considered rough approximations. Nevertheless, the calculations generally show that transport of injected fluids by hydrodynamic flow is not presently a serious hazard in Ohio.

COLUMBUS, NATHAN, Tahal Consulting Engineers, Ltd., Tel Aviv, Israel

DAN REGION, ISRAEL, SEWAGE-RECLAMATION RECHARGE PROJECT

The Dan Metropolitan Region, Israel, consists of about 1 million inhabitants, about 50% of whom live in the city of Tel Aviv and the rest in surrounding communities.

The industrial, economic, and commercial growth of this region has been rapid in recent years and the ef-

fluent forecast in 1980 is estimated at more than 100,000 cu m (80,000 acre-ft) per year, and 175,000 cu m (140,000 acre-ft) in the year 2000.

The sewage-reclamation recharge project was conceived to solve both environmental hazards and water-resources management problems and consists of 2 phases, sewage reclamation and recharge of the reclaimed sewage.

The project provides for treatment of the sewage in a series of oxidation ponds and pumping to nearby spreading grounds after detention in the terminal pond. Recharge operations will begin in 1973 with the recharge of 7,500 cu m/year; the scope of these operations is to be stepped up gradually to reach 50,000 cu m by 1980. The spreading grounds cover an area of 250 acres and are about 0.7 mi from the oxidation ponds.

The area occupied by the spreading grounds consists of sand dunes, overlying, for the most part, calcareous sandstones. These formations constitute the main aquifer of the region. The reclaimed sewage will be spread alternately to allow the grounds to be dried and cultivated between recharge operations in order to remove the surficial crust and increase infiltration. It is estimated that the rate of percolation will be about 6 in./day.

An array of 30 production wells—drilled for the specific purpose of exploiting the recharged water—surrounds the spreading grounds at a distance of 0.3 mi from its perimeter. The quality of the recharged water is satisfactory from the content of nitrogen compounds (less than 10 ppm), phosphates (less than 1 ppm), and bacteria and virus. As an additional precaution, the water will be held in the subsurface for a period of 400 days, during which it will undergo natural filtration and mixing with existing groundwater. Furthermore, the recharge operations will allow regulation of supply and demand according to existing conditions.

Following its subsurface movement and mixing, the reclaimed water will be pumped and conveyed to the National Water Carrier for transfer to the southern area of the country for supplementing irrigation requirements.

DENNISON, ERROL G., and FRANK SIMPSON,
Saskatchewan Dept. Mineral Resources, Regina, Saskatchewan, Canada

HYDROGEOLOGIC AND ECONOMIC FACTORS IN DECISION MAKING UNDER UNCERTAINTY FOR NORMATIVE SUBSURFACE DISPOSAL OF FLUID WASTES, NORTHERN WILLISTON BASIN, SASKATCHEWAN, CANADA

The normative subsurface waste-disposal condition of no hazard to population, coupled with optimum allocation of drilling funds, can be achieved best through search for primary and alternative disposal formations by evaluation of hydrogeologic data on a basinwide scale. Any decision to drill a disposal well in Saskatchewan is made under considerable uncertainty, which is a reflection of the present reconnaissance level of subsurface information.

Subsurface disposal of fluid wastes in the Williston basin region is largely restricted to sandstone and carbonate aquifers (Cambrian through Lower Cretaceous) of the Saskatchewan-Manitoba tectonic shelf: (1) oil-field brines (at rates of the order of 15 gpm); (2) waste brines from exploitation of Devonian potash deposits (up to 750 gpm); (3) waste brines from solution mining of LPG-storage caverns in Devonian halite (up to 300 gpm); (4) refinery sour water

and spent caustic (up to 20 gpm); and (5) chlor-alkali-plant wastes (up to 15 gpm), partly associated with previously injected herbicide wastes.

Hydrogeologic constraints on development of subsurface waste-disposal systems, not related to reservoir quality of disposal formations but likely to influence waste migration, are (1) proximity of the outcrop belt on the north and east, (2) pre-Cretaceous valley systems controlling development of fluvial channels up to the present, (3) sinks formed through localized solution of Paleozoic halite, and (4) positive basement features and related overlying structures.

Estimated ultimate capital investments for existing Saskatchewan injection systems range from \$20,000 to \$100,000 in the oil fields, to more than \$300,000 for some potash-brine disposal wells, and are determined largely by depth of disposal formation, drilling technique, and well design. Potash-brine disposal wells in the vicinity of shaft mines include the most costly and refined systems, and involve directional drilling to formations below the potash unit and mud programs employing fluids compatible with evaporite minerals.

DrTOMMASO, ANTHONY, and GERALD H. ELKAN, Dept. Microbiology, North Carolina State Univ., Raleigh, N.C.

ROLE OF BACTERIA IN DECOMPOSITION OF INJECTED LIQUID WASTE AT WILMINGTON, NORTH CAROLINA

In 1968, Hercules Chemical, Inc., Wilmington, North Carolina, began injecting organic waste through wells into a saline-disposal zone at depths of 850–1,000 ft. The waste, which is a by-product of dimethyl terephthalate used in the production of synthetic fiber, is composed of water, with a pH of about 4.0, containing approximately 15,000 ppm acetic acid, 5,000 ppm formic acid, and 500 ppm methanol.

The movement and composition of the transformed waste have been monitored by a network of 14 observation wells drilled to various depths. The waste-water analysis and monitoring were performed by the U.S. Geological Survey.

In June 1972, waste was detected in observation well 14. The microbial population was periodically sampled as the dissolved organic carbon fraction increased. The dissolved organic content increased to 112 mg/l, and then rapidly decreased to 20 mg/l. This sudden decrease in dissolved organic carbon was accompanied by the appearance of gas composed of approximately 60% methane. Each time a decrease in dissolved organic carbon occurred, gas was found and an increase in the total microbial population was measured.

Methane gas production is the result of microbial activity. The injected waste contains adequate carbon and energy substrates for the strictly anaerobic, methane-producing bacteria which have been isolated from well 14. In addition to the methane-producing bacteria, other bacteria have been isolated and identified. Microorganisms such as *Agrobacterium*, *Pseudomonas* (especially species *fluorescens*), *Proteus*, *Bacillus*, *Arthrobacter*, *Aerobacter*, *Corynebacterium*, and *Staphylococcus* have been observed. The total microbial population was found to be 25×10^6 organisms per milliliter in well 14 and 30×10^8 organisms per milliliter in the unpolluted aquifer. The source of these bacteria is the natural aquifer, inasmuch as the injected waste is sterile. The waste alone does not support a microbial population for it contains no nitrogen. Such nitrogen substrate is apparently supplied by the natural water in the aquifer.