separation. Towed electrical measurements are complementary to high-resolution subbottom profiling.

Sediment samples collected from Heald Bank were placed in a small wooden trough to appraise some of the properties that control the sediments' resistance and spontaneous potential as well as to obtain insight into the relation between depth of measurement with various electrode spacings. The experimental electrical studies show the same spontaneous potential variations as were found over Heald Bank.

- HAWKINS, G. P., Union Oil Co. of California, New Orleans, La., C. F. DODGE, Dept. of Geology, Univ. of Texas at Arlington, Arlington, Tex., and J. C. BUTLER, Dept. of Geology, Univ. of Houston, Houston, Tex.
- Clay Mineralogy of Lewisville Member of Cretaceous Woodbine Formation in Arlington, Tarrant County, Texas, Area

One hundred clay-sized samples selected from two cores and two measured sections of the Lewisville Member, three samples from the overlying Arlington Member, and five from the underlying Dexter Member of the Cretaceous Woodbine Formation in eastern Tarrant County, Texas, were analyzed. The amounts of each clay mineral present were calculated from X-ray diffractograms of natural, ethylene glycol-saturated, and heated samples. The average clay mineral assemblage was approximately 28 percent illite, 36 percent kaolinite, and 36 percent expandable lattice clays.

Floral and faunal assemblages and sedimentary structures demonstrate that the Lewisville Member in the Arlington area is part of a deltaic interdistributary complex association where admixing of fresh and saline water creates a transition zone. Vertical changes in clay-mineral distributions correlate well with the changes in depositional environments from fluvial to swamps and bays and finally to marine by the end of Lewisville deposition. Apparently for the Lewisville Member specifically, and probably for the Woodbine Formation in general, clay-mineral distributions are environmentally significant.

The predominant expandable lattice clay in the Lewisville Member is Ca-Mg montmorillonite. In his studies of the Woodbine in east-central Texas, Beall found these exchangeable cations to be most abundant in nearshore sediments with Na + cation content increasing basinward, reflecting the more marine character of the sediments.

Kaolinite is the most abundant clay mineral in the five Dexter Member samples and in samples from the lower 5 to 10 ft of the Lewisville Member. Several lenticular channels, extensive sands, and interbedded silts and clays provide evidence that the Dexter Member is part of the meander-belt facies. The basal Lewisville marks the transition between a fluvial environment below and swamp and bay environments above.

Randomly interstratified montmorillonite/illite is present throughout the sampled intervals, but no clear relation between this type of clay and depositional environment is apparent, as the semiquantitative method used in this investigation is useful only in determining the relative amounts of the end members of the mixed-layer clay.

An increase in kaolinite and expandable-lattice clays with respect to the average composition in the upper Lewisville and in three Arlington Member samples reflects an increase in transport energy and a westward shift in the strandline.

HOLLAND, D. S., and C. E. SUTLEY, Pennzoil Co., and R. E. BERLITZ and J. A. GILREATH, Schlumberger Offshore, Houston, Tex.

East Cameron Block 270, Pleistocene Field

Exploration of the Pliocene-Pleistocene in the Gulf of Mexico since 1970 has resulted in the discovery of significant hydrocarbon reserves. One of the better gas fields has been the Block 270 East Cameron field. Utilization of a coordinated exploration plan with Schlumberger has allowed Pennzoil as operator to develop and put on production the Block 270 field in minimum time.

Block 270 field is a north-south trending faulted nose at 6,000 ft. At "G" sand depth (8,700 ft) the structure has closed, forming an elongated north-south structure with dip in all directions from the Block 270 area. Closure is the result of contemporaneous growth of the east-bounding regional fault.

Structural and stratigraphic interpretations from dipmeters were used to help determine the most favorable offset locations. The producing zones were found to consist of various combinations of barlike, channellike, and distributary-front sands. The sediment source for most of the producing zones was southwest of the area. However, two zones are exceptions and derived sediments from the north through a system of channels parallel with the east-bounding fault.

Computed logs were used to convert conventional logging measurements into a more readily usable form for evaluation. The computed results were used for reserve calculations, reservoir quality determinations, and confirmation of depositional environments as determined from other sources.

KOCURKO, M. J., Union Oil Co. of California

Modern and Ancient Reef Complexes and Associated Limestone Diagenesis of San Andres Island, Colombia

San Andres is a small coralline island 136 km east of the Caribbean coast of Nicaragua. Surface mapping and paleontologic data indicate reefs have been growing actively in the area at least since early Miocene time. Because of the offlap relations of the ancient reef complexes, accessibility of progressively younger rocks is simplified.

Field and laboratory examination of both modern and ancient reef complexes indicates five major bottom facies: (1) forereef flank, (2) reef, (3) backreef platform, (4) backreef lagoon with patch reefs, and (5) shore area. Principal builders of the reefs were *Millepora* and lime-secreting algae with abundant *Acropora*, *Diploria*, *Montastrea*, and *Porites*.

From X-ray and petrographic studies of the limestones, a sequence of carbonate diagenesis has been determined for the San Andres area. During early stages of diagenesis, sediments initially are cemented by grain welding and aragonite precipitation between grains. This early type of cementation is most common in the supertidal and intertidal zones. Subsequent calcite cementation occurs by dissolution-precipitation after aragonite. After calcite precipitation, no evidence can be found of the preexisting aragonite cement. Although inversion of aragonite to calcite commonly occurs in grain material, dissolution-precipitation seems to be the major process of cementation.

During the diagenetic sequence, four responses may be expected: (1) magnesium is removed and high-magnesium calcite stabilizes to low-magnesium calcite, (2) aragonite can stabilize to calcite, (3) aragonite may be dissolved, and (4) sediments may become dolomitized. The time required for any of these reactions is variable and depends on the chemical environment. X-ray analyses indicate that all samples older than middle Pleistocene have stabilized to low-magnesium calcite or dolomite. The result of the diagenetic sequence is the development of a low-magnesium calcite limestone, a dolomite, or a combination of the two.

Porosity in the San Andres area is primary, secondary, or occluded and development depends on exposure of carbonate material to a subaerial environment before mineral stabilization occurs.

KUPFER, D. L., Louisiana State Univ., Baton Rouge, La.

Shear Zones in Salt-Dome Stocks Delineate Spines of Movement

Ever since Balk's studies of the 1940s, the idea has been grow-

ing that the salt of a stock moves vertically upward in several unit cylinders called "spines." Observations in the salt mines of the Five Islands trend in south Louisiana confirm this interpretation. In some places the spines are defined by sedimentary gouge (shale, sand, limestone), which becomes included in the salt core and clearly marks the spine boundaries. These boundary shear zones can extend from the edge of the salt to the very center of the stock. Shear zones that have a diameter of 1,000 to 4,000 ft have been observed in four of the five mines. Every gradation exists from relatively simple, thin (15 ft), linear shear zones, to wider (400 ft) ones that have been twisted and sheared into the salt in complicated patterns by later salt movements.

The shear zones can be traced upward through the salt to surface irregularities in the salt-stock surface, and into topographic irregularities on the ground surface (generally valleys). Disruptions of the overlying domal sedimentary rocks also can be recognized, and Balk and Muehlberger suggested these as the cause of the irregular salt motion. The present analysis suggests, however, that the salt spines cause the overlying strata disruptions.

McCUNN, H. J., Tomlinson Instruments, Inc., Houston, Tex.

Model Study of Morphologies Caused by Exploding Superheated Vapor and Possible Lunar Analogues

Hypervelocity cosmic bodies impacting on the lunar surface create volumes of vaporized rock materials which react in thermal agitation with the lunar soils. Water drops falling onto a surface of hot silt provide a model for the thermal agitation process, and produce several distinctive types of craters which appear to have exact analogues on the lunar surface. Surprisingly, the interaction between the silt and vaporizing water is not always the same and at least three types of reaction occur, each producing a distinctive crater morphology.

In one type of reaction the blast triggers the formation of an outwardly expanding rolling ring of vapor and rock debris. The expanding ring digs a crater which has slump features around the rim, and the inwardly rolling motion piles up materials in the center to form a cone. If the depth of silt is shallow, the same reaction creates a flat-bottomed crater with slump rings.

A second type of reaction occurs where the vaporized materials rotate horizontally in a swirling motion. This type of action creates concentric multiple craters and chains or lines of coalesced craters. Swirl-like slumps of debris are left in the bottoms of some of the craters whereas in others the wall may be breached and the material flows away leaving a rillelike trail.

A third reaction occurs where the impact is violently explosive, and the materials are blown from the crater. These craters have blast rays and generally have smoothly sloping bottoms which contain a minimum of debris.

Photographs of features observed in the model studies compare with photographs of analogous features on the surface of the moon and have implications as to the origin of the lunar surface.

McGHEE, B. F., J. S. BLACKBURN, and B. C. LEACH, Schlumberger Well Services, Houston, Tex.

Dual Spacing Thermal Neutron Decay Time Log: Cased-Hole Exploration Tool

Geologists are being called on to find more oil and gas, much of it in existing fields. Schlumberger's dual spacing thermal neutron decay time log helps locate bypassed oil and gas productive zones. It can be used to evaluate these zones and to evaluate other zones which were not analyzed properly before initial completion of the well. The dual spacing thermal neutron decay time log also may be used to monitor reservoirs during their productive life to assure maximum production. McMICHAEL, C. E., Shell Oil Co., New Orleans, La.

Oil Industry Experience in Louisiana Offshore, 1946-1972

This study covers industry's activities in the State and Federal parts of the Louisiana offshore from the first State lease sales immediately after the close of World War II through the Federal sales held in 1972. Estimates of future exploration and development on these leases are included and a model of the operation during the remainder of the productive life is used to evaluate the outcome.

The area has become an important producing province (1973 production was about 450 million bbl of oil and condensate and 3.9 Tcf of gas) and the leases acquired through 1972 may result in the discovery of as much as 8.4 billion bbl of oil and condensate and 70.4 Tcf of gas. Lease purchase and exploration costs (including future costs on leases acquired prior to the end of 1972) total about 8.2 billion dollars and development costs will be at least 11.4 billion when these leases are developed fully. The profutability of the venture for industry will depend on future product prices. At the end of 1973, 48 percent of the oil and 37 percent of the gas had been produced.

When the original study was done in mid-1973, two future price cases were analyzed. Case I incorporated the mid-1973 revenue levels through the remainder of the productive life. In Case II, oil prices were increased 5 percent per year and gas, 6.50 percent. These increases were based on published estimates of future world oil priced by Federal agencies and major banks. An additional case will be presented using future prices in keeping with recent events in the world oil market. This case also will incorporate any changes in the industry tax structure as a result of legislation now pending in Congress.

Industry's overall results have been poor except for the early years. The latter period, 1968-1972, will yield a poor return under almost any reasonable assumption of future prices. The deterioration in profitability from the early to late period is partly due to a moderate decline in field quality as well as higher development and operating costs. (The newer fields are generally in deeper water and farther from shore.) However, the major cause is the much higher prices paid for leases at the more recent sales. Even in Case II, about 3/3 of the operating profit from the 1968-1972 period will be paid to the Federal treasury in the form of bonus, rentals, royalty, and income tax. Depending on future prices, this can amount to as much as 50 percent of gross revenue. This does not include any provision for excess profits or excise taxes which would increase the Federal share or benefits to the consumer as a result of price constraints on domestic production to keep revenues below world oil prices.

MURRALL, R. S., Dept. of Geology, Florida State Univ., Tallahassee, Fla.

Wave Characteristics with Restricted Fetch: Case Study of Lake Okeechobee

In the design of earth work constructions along rivers and lakes, it is important to know the relations between wind and the waves. Such observations are a first stage in a complete investigation of wave effects on beaches and earth structures of different shapes and materials. The generally used form of these relations deals with deepwater conditions, where the fetch is unlimited. Such relations cannot be applied to small lakes and protected bays.

The earliest work in this field was that of Johnson on Clear Lake, California. He concluded that wind duration but not fetch was the controlling factor in any kind of change in wave characteristics. Later, on the basis of the study of Abbots Lagoon, California, Johnson showed that the dimensionless term gf/u^2 is useful in estimating wave conditions within certain limits. Burling compared the wave data from Staines reservoir with the data