

WC02

SUCCESSFUL GRAVEL PACKING OF A HORIZONTAL WELL WITH LIMITED CLEARANCE

David Subero, Schlumberger DOWELL, David Attong, BPAECTT, Carla Suite, BPAECTT

This paper was prepared for presentation at the GSTT 2000 SPE Conference held in Port of Spain, Trinidad 10-13 July 2000. It was selected for presentation by a Technical Committee following review of the information contained in an abstract submitted by the author(s). Contents of the paper, as presented, have not been reviewed by this Technical Committee and are subject to correction by the author(s). The material, as presented, does not necessarily reflect any position of the Technical Committee, Geological Society of Trinidad and Tobago, Society of Petroleum Engineers, its officers, or members. Copies of papers should contain conspicuous acknowledgement of where and by whom the paper was presented.

Abstract

In August 1999, BP Amoco Energy Company of Trinidad & Tobago successfully gravel packed a 600 ft. horizontal well with limited clearance (0.39") between screens and liner.

The Teak B-8 offshore well was completed as a 600 ft gravel packed horizontal completion across a 5" pre-perforated liner (4.276"ID). What was unusual about this wellbore configuration was that 2-7/8" Excluder screens (3.89"OD) were run instead of the popular 2-3/8" Excluder size. The 5" liner was a contingency plan to the original 6" open hole in the event of shale activity, however no contingency was placed on screen size due to equipment logistics. The Horizontal gravel pack

design simulation indicated that even with limited clearance it was possible to gravel pack the lateral section, even though global experience was to exclusively use 2-3/8" screens in any 5" liner. The work was done with a 460K Snubbing Unit. See Fig.1 for wellbore sketch. Production rates have exceeded expectations, from 1100 BOPD to 2000 BOPD to 2500 BOPD at 28/64" to 32/64" to 36/64" adjustable choke settings, FTP dropped from 600 psig to 590 psig to 580 psig for the above rates. This indicates an extremely high productivity index. No sand is produced.

With careful planning and execution, risks associated with limited clearance can be reduced in gravel packing horizontal sections. For successfully gravel packing a 6" hole with a 5" pre-perforated liner and 2 7/8" screens, the most salient control parameter is the dune height selection which dictates the successful progression of the alpha waves from the heel to the toe. Thereafter, the successful progression of the beta waves is indifferent to the existence of the 5" pre-perforated liner.

Completion objectives were achieved by effective co-ordination within a multi-disciplinary team framework.

Manuscript Not Submitted